

### General Specs

#### Sweep Path:

Main broom only: 60"  
 Main broom & one side broom: 90"  
 Main broom and 2 side Brooms: 120"

Chassis Commercial Class 7

Wheel Base Chassis dependent

Warranty Sweeper, 1 year parts & labor

### Sweeper Engine

Make Cummins B 3.3

Type 4 cylinder

Displacement 3.3 L

Horsepower 74 @ 2600 RPM

Torque 181 lb. ft. (245 Nm)

Aspiration Turbo charged

### Main Broom

Type Prefab disposable Polypropylene filled

Diameter 34" (864 mm)

Broom Material Polypropylene

Length 60" (1,473 mm)

Core Type Disposable steel tube

Speed Variable with engine RPM

Drive Hydraulic motor with direct drive

#### Digging Pressure & Wear Control

Closed loop control hydraulic spring

Lift control Hydraulic

Mounting Full-floating trailing arm

Down Pressure Indicator In-cab dial

### Side Broom

Type Disposable 5 or 6 segment, plastic

Diameter 46" (1,168 mm)

Broom material 26" wire (660 mm)

Disc Construction Steel

Speed Reversible and variable with engine RPM

Drive Full hydraulic

#### Digging Pressure & Wear Control

Pneumatic spring

Lift control Pneumatic

Flexibility Free-floating and full side-ways oscillation

Mounting Trailing Arm

Down Pressure Indicator In-cab gauge

### Conveyor

Type Belt with molded-in rubber cleats

Material (belt) Rubber reinforced fabric

Speed Variable with auxiliary engine RPM

Cleat Clearance Settable 1" to 4", in cab raisable up to 6" while sweeping

Adjustment Jack screw

Lift Control Hydraulic

Cascade Washdown With fill diverter

### Instrumentation/Controls

#### Warning Lamps & Chime

Low hydraulic oil

Conveyor stall

#### Warning Lamps

Hydraulic oil temperature

Hydraulic oil filter restriction

Low water spray

Broom position

Hopper position

Water tank level

### Electrical System (Sweeper)

#### Twelve Volt Negative Ground System

60 amp alternator

Battery 12v 1000 CCA

Circuit Protection Activated by ignition switched constant duty solenoid (except lights).

Wiring Hot stamp identified with weatherproof connectors

### Hydraulic System (Sweeper)

Sweep System Pump Triple section gear pump

Capacity 13.5 GPM @ 1200 RPM

Fittings O-ring face seal

Reservoir Capacity 35 gal (132 l)

Inlet strainer 100 mesh

Return filter 6 micron

Filter Restriction Indicator

Breather 10 micron

Cooler Externally mounted

Valves Electro-hydraulic

### Hopper

Volumetric Capacity 4.5 yd<sup>3</sup> (3.4 m<sup>3</sup>)

Material volume 3.3 yd<sup>3</sup> (2.5 m<sup>3</sup>)

#### Hopper Lift and Dump Controls

Electro/Hydraulic in-cab

#### Inspection Door

#### Offload

##### Right Side

Minimum dump height 38" (965 mm)

Maximum dump height 10' (3,048 mm)

Maximum hopper dump angle 50°

Design Lift capacity 10,000 lbs (4545kgs)

Lifting mechanism Two stage with hydraulic cylinders

### Water Spray System

Tank construction Polyethylene

Tank capacity 360 gals (1362 l)

Fill Hose 16' 8" (5080 mm) with 2.5" (64 mm) NST hydrant coupling

Pump Electric diaphragm

Spray nozzles 3 across main broom and over each gutter broom

Water Filter 80 mesh plastic housing

Controls In cab pump control and flow control valves at each side broom



### Available Enhancements

- LED strobe
- Arrow stick
- Automatic lubrication system
- Fire extinguisher
- Broom camera system (rear standard)
- Front spray bar
- Hydrant wrench
- Lighting bundles
- Squeegee with rubber edging
- Extended side broom reach
- In-cab controlled variable speed side brooms

### Paint

Body: High-gloss white powdercoat

Custom colors available

Undercarriage:

Grey powdercoat

### Chassis

Autocar Xpert, Freightliner M2, or International 4300.

Contact your Elgin Dealer for detailed chassis specifications.

### Warranty


#### Sweeper

1 year parts and labor

#### Engine

Consult Factory

Your Elgin Dealer is:



Elgin Sweeper Company  
 1300 W. Bartlett Rd.  
 Elgin, Illinois, U.S.A. 60120-7529  
 847-741-5370 Phone  
 847-742-3035 Fax  
 www.elginsweeper.com

Effective 01/14

Specifications subject to change without notice.

P/N 0705395

© 2014 Elgin Sweeper Company

Federal Signal Corporation is listed on the NYSE by the symbol FSS